



Product Specification and Technical Data

PRODUCT: BG Diesel Care

PART NO.: 229

TEST DATA:	Test	ASTM Test Method	Typical Test Results
	API Gravity @ 15.6°C (60°F)	D287	36.9
	Specific Gravity @ 15.6°C (60°F).	D1298	0.8402
	Density,		
	U.S. lbs./gal. (kg/m ³) @ 15.6°C (60°F)	D1250	7.005 (839.384)
	Flash Point, PMCC	D93	43°C (110°F)
	Viscosity, cSt @ 40°C (104°F).	D445	1.37
	Initial Boiling Point	D86	152°C (307°F)
	Pour Point	D97	-46°C (-50°F)
	Color	D1500	L1.0
	Color	Visual.	Straw

PROBLEM: Diesel engines are prone to the buildup of combustion deposits. These deposits decrease fuel economy, deform injector spray patterns, increase exhaust emissions, and lead to hard starts.

SOLUTION: BG Diesel Care cleans diesel fuel injection systems, restores optimum fuel efficiency and protects from the abrasiveness of low sulfur fuel.

- Mixes with all diesel fuels
- Contains no alcohol
- Complies with federal low sulfur content requirements
- Catalytic converter, diesel particulate filter and oxygen sensor safe

BENEFITS:

- Restores fuel efficiency
- Restores engine performance
- Restores horsepower
- Reduces harmful exhaust

USAGE: Follow procedures supplied with the BG Diesel VIA® supply tool. Not designed for use in the fuel tank. Safe for all fuel system components.

BG Products, Inc., accepts no liability for excessive use or misuse of this product.