



Product Specification and Technical Data

PRODUCT: BG SAE 0W-20 Full Synthetic Engine Oil

PART NO.: 729

TEST DATA: Test	ASTM Test Method	Typical Test Results
API Gravity @ 15.6°C (60°F)	D287	37.0
Specific Gravity @ 15.6°C (60°F).	D1298	0.8397
Density,		
U.S. lbs./gal. (kg/m ³) @ 15.6°C (60°F)	D1250	7.008 (839.7)
Viscosity, cSt @ 40°C (104°F).	D445	44.78
Viscosity, cSt @ 100°C (212°F)	D445	8.84
Viscosity Index	D2270182
Flash Point, Grabner	D7094	206°C (403°F)
Viscosity, cP @ -35°C (-31°F)	D5293	3,890
Pour Point	D6749	-39°C (-38°F)
Noack Volatility, % Loss	D5800	11.5
Color	D1500	3.0
Color	Visual.Amber

DESCRIPTION: BG SAE 0W-20 Full Synthetic Engine Oil flows immediately to lubricate vital engine components for easy cold weather starts and provides outstanding high temperature protection. It features a low evaporation rate as well as enhanced thermal and oxidative stability.

USAGE: BG SAE 0W-20 Full Synthetic Engine Oil is designed for gasoline passenger cars, vans and light trucks requiring API SN Plus and preceding engine oil. It is recommended for use in vehicles factory-filled with SAE 0W-20 or SAE 5W-20 engine oil. Use in accordance with engine manufacturer’s recommendations. **FOR PROFESSIONAL USE.**

BG Products, Inc., accepts no liability for excessive use or misuse of this product.