



Product Specification and Technical Data

PRODUCT: BG Hi-LOW30
SAE 0W-30 Full Synthetic Engine Oil

PART NO.: 730

TEST DATA:	Test	ASTM Test Method	Typical Test Results
	API Gravity @ 15.6°C (60°F)	D287	36.6
	Specific Gravity @ 15.6°C (60°F)	D1298	0.8415
	Density, U.S. lbs./gal. (kg/m ³) @ 15.6°C (60°F)	D1250	7.023 (841.5)
	Viscosity, cSt @ 40°C (104°F)	D445	59.18
	Viscosity, cSt @ 100°C (212°F)	D445	10.89
	Viscosity Index	D2270	178
	Flash Point, Grabner	D7094	208°C (406°F)
	Viscosity, cP @ -35°C (-31°F)	D2270	5283
	Pour Point	D6749	-38°C (-37°F)
	Noack Volatility, % Loss	D5800	12.2
	Color	D1500	3.0
	Color	Visual	Amber

DESCRIPTION: BG Hi-LOW30 is a revolutionary full synthetic engine oil utilizing the most shear stable polymer technology available. It flows immediately to lubricate vital engine components and prevent wear even at very low temperatures. It resists thermal oxidation, evaporation, viscosity increase (thickening) and provides a long drain life of 15,000 miles (25,000 km) or one year. BG Hi-LOW30 is formulated with premium levels of detergent/dispersants to keep the engine clean.

USAGE: BG Hi-LOW30 is designed for passenger cars, vans and light trucks requiring API SN Plus and preceding engine oil. It is recommended for use in vehicles factory-filled with a full synthetic 0W-20, 5W-20, 0W-30, 5W-30 or 10W-30 engine oil. Use in accordance with engine manufacturer’s recommendations. FOR PROFESSIONAL USE.

BG Products, Inc., accepts no liability for excessive use or misuse of this product.